Services Support



Big Foot H Frame

Pipework | Ductwork | Cable Trays

Typical Application

The H Frame Set is a quick, versatile and economical solution for supporting pipework, ductwork, cable trays or any combination of these. You provide your own strut, keeping the duct and pipe installations low cost and totally flexible by fabricating the frameworks on-site.

Using inserts, the feet adapt to accomodate 41mm x 41mm off-the-shelf strut. The majority of installations require 305mm H Frames but where a greater load spread is required 450mm and 600mm H Frames are also available.

Kit Includes


- 2 x Plastic feet
- 2 x Anti-vibration mats
- 2 x Strut inserts
- Brackets and fixings
- Assembly instructions

PLEASE NOTE: Strut is not included

FEET FLEECES

Recommended for use on PVC membrane roof surfaces to prevent migration of plasticizers.

ANGLED AV MATS 2.5° and 5° AV mats are also available for sloped roofs.



Material Specification

Nylon 6 B601L 30% Glass Fibre Filled

ANTI-VIBRATION MAT

SBR-Recycled Rubber. Bound using a ratio of high quality moisture curing Polyurethane Pre-Polymer. BS7188:1989 & BS5696 Part 3:1979

BRACKET

Hot Dip Galvanised Mild Steel: BS EN 10219-1:1997. Welding Standard: BS EN ISO 15614-1 Galvanising: BS EN ISO 1461:1999 Salt Mist Testing: BSEN60068-2-52 Test Kb Severity 1

WORKING CONDITIONS

Suitable for internal or external applications in temperatures between -40°C to +80°C

Technical Information

Model	Part No.	Foot Size (mm)	Rec. Loading per Frame (kg)	Packaged Weight ^(kg)
Small	B6088	305	150	6.75
Large	B6089	450	300	13.35
Mega	B9222	600	450	20

PROVIDE YOUR OWN STRUT KEEPING INSTALLATIONS LOW COST AND TOTALLY PRANEWORKS ON-SITE INFRAMEWORKS ON-SITE INFRAMEWORKS ON-SITE INFRAMEWORKS ON-SITE INFRAMEWORKS ON-SITE INFO